

REARS

Engine Drive Powerblast 38" single fan



POWERBLAST

# engine drive **powerblast** sprayer

## single **38"** diameter fan

<b>length</b>	20' 6"
<b>height</b>	63"-70" to fan housing/adjustable
<b>width</b>	105" (21.5L-16.1/adjustable axle)
<b>tire options</b>	16.5L-16.1 rib or terra 21.5L-16.1 rib or terra 11.25-24 rib
<b>axle options</b>	multiposition adjustable fixed offset (specify)

John Deere <i>Powertech</i> 4.5L diesel engine 115 horsepower turbocharged	38" diameter 9 blade stainless steel axial flow fan operating @2200RPM
Electric throttle	SS304 stainless steel blower housing
Vibration dampener on flywheel minimizes drivetrain vibration	Electric fan clutch
Large surface easy clean radiator	Lower air scoops
50 gallon fuel capacity	500 gallon stainless steel tank stainless steel plumbing, lid assembly
Safety shut down system	stainless steel large paddle mechanical agitation stainless steel tank rails, engine shroud
Oil pressure	Rears RPA centrifugal pump
Water temperature	80GPM/200PSI
Control from the cab	Electric pump clutch
Throttle	Electric spray controls
Spray manifold	Electric dump valve
Dump valve	Strainers on suction line and discharge line Strainers are easily isolated for cleaning
Emergency Shut Down	Rollover nozzles with ceramic tips
Instrumentation	Diaphragm check valves on each nozzle for positive shut-off
Ammeter	Adjustable swivel hitch
Tachometer	
Oil pressure	
Water temperature	
Hour meter	
Air cleaner service indicator	

If you need help with any Rears product, or have an application question, one of our dealers will be happy to help. We have collected a nationwide network of the most helpful and outgoing professionals in the business who want nothing but to help you do your job more easily.

For dealer information, call our offices in Oregon:

**1 800 547 8925**

Dealer:

Our promotional are printed on recycled paper.  
Please keep this circle going. Recycle this sheet.



Litho USA

rears manufacturing company. eugene. oregon. 1 800 547 8925

**REARS**